

Contour Stretch— Ultrafabrics®



Ultraleather® Contour Stretch features breathable technology that enhances acoustical properties. As with other Ultraleather products, Contour is engineered with top quality composition including polycarbonate resins, to ensure lasting performance. Contour is made specifically to extend smoothly around curves and crevices for a tight, seamless fit.

Distinctive Features

- Superior durability — industry-leading 14+ weeks hydrolysis results
- Blended backcloth for expanded upholstery capabilities
- Multi-Directional Stretch
- Bleach cleanable (1:5 bleach/water solution)
- Notable acoustic properties, when paired with 1” fiberglass infill, for sound absorption



Contour Stretch— Ultrafabrics®



Specifications

Description

Textured Ultraleather®

Composition

Proprietary FR treatment, 100% Polyurethane Surface, 80% Rayon and 20% Nylon

General

Roll Size: 33 yards (+/- 10%)

Width: 54" (+/- 10%)

Weight: 8.09 oz/sq yd / 274 g/sm (+/- 10%)

Thickness: 0.77mm / .03" (+/- 10%)

Stretch Percent: 50% Warp, 75% Fill

Set Percent: 7% Warp, 16% Fill

ULCOFR MEETS:

Test	Method
60 second Vertical Burn Test	FAR 25.853(a) Appendix F, Part I,(a), 1(i):60sec
12 Second Vertical Burn	FAR 25.853(a) Appendix F, Part I,(a), 1(ii):12sec
Seat Cushion with Fireblock	FAR 25.853 (b) Appendix F, Part II
Abrasion Test	ASTM D3884 Taber Method, 2,000 cycles
Breaking Force	ASTM D5034: Warp- 40, Fill- 25
Colorfastness to Light	AATCC 16.3, 200 hours Grade 4-5
Colorfastness to Crocking	AATCC 8: Grade 5