Raffia— Ultrafabrics®



Delivering modern carbon-fiber patterning, Raffia is highlighted by a unique prismatic affect for added textural allure. Raffia is the perfect material to add an elevated look in accents and vertical surfaces

Distinctive Features

•Superior durability — industry-leading 14+ weeks hydrolysis results





www.tapiscorp.com | @tapiscorp

App: JH 2/28/2022 Revised: 12/16/2022

Raffia—

Ultrafabrics®



Specifications

Description

Textured Ultraleather®

Composition

Proprietary FR treatment, 100% Polyurethane Surface, 100% Reinforced Rayon Backing

General

Roll Size: 33 yards (+/- 10%)

Width: 54" (+/- 10%)

Weight: 12.7 oz/sq yd /430 g/sm (+/- 10%)

Thickness: 1.12 mm / 0.44" (+/- 10%) Stretch Percent: 1.2% Warp, 24% Fill Set Percent: 0.1% Warp, 0.4% Fill

ULRAFR Meets:

| Test | Method |
|------------------------------|---|
| 60 second Vertical Burn Test | FAR 25.853(a) Appendix F, Part I,(a), 1(i):60sec |
| 12 Second Vertical Burn | FAR 25.853(a) Appendix F, Part I,(a), 1(ii):12sec |
| Seat Cushion with Fireblock | FAR 25.853 (b) Appendix F, Part II |
| Abrasion Test | ASTM D4157 Wyzenbeek method 400,000 double rubs |
| Breaking Force | ASTM D5034: Warp- 107.6 min, Fill- 89.8-max |
| Colorfastness to Light | AATCC 16.3, 200 hours Grade 4-5 |
| Colorfastness to Crocking | AATCC 8: Grade 5 |



